



All Trailer Spares

All Trailer Spares (Australia) Pty Ltd

A.C.N. 081 545 011

Importers and Distributors of Trailer Spare Parts

605 Toohey Road, Salisbury Qld 4107,

P O Box 176, Salisbury Qld 4107

PH (07) 3277 2802 Fax (07) 3277 2483

FACT SHEET

JOCKEY WHEELS AND STANDS

The purpose of this group of products is to support the drawbar of your trailer or caravan and to facilitate the easy attachment and removal from your tow vehicle.

Careful selection of the correct jockey wheel or stand is critical for both your safety and the ease of use.

Lets examine the different types and how they may best suit you and your trailer.

6" LIGHT DUTY: 350kg Static Load.

Most suitable where the jockey wheel is used on smooth ground.

Standard 6" Jockey Wheel. Perfect for the standard box or boat trailer that is used infrequently. This is the type that is clamped to the drawbar and then removed after the trailer is connected to the tow vehicle. Available in two lengths, standard and extra height.

Swingaway 6" Jockey Wheel. If you work with your trailer daily or use your boat often, you may want the convenience of the swingaway type of jockey wheel that remains fixed to the drawbar and simply swings 90 degrees up out of the way when not required. They can be attached by welding, bolted through the drawbar or with the correct bracket, held in place with 'U' bolts.

8" MEDIUM/HEAVY DUTY: Up to 750kg Static Load.

These Jockey Wheels typically have an 8" wheel of either solid rubber or a steel rim with a solid rubber tyre. Selection is largely personal preference, although the steel rim type offers an additional 50kg capacity and roller bearings.

Common applications include: Plant trailers, Camper trailers, larger Boat trailers, or trailers used on rough ground where an easier rolling wheel is required.

Standard 8" Jockey Wheel. Available with a solid rubber or steel rim. Available in two lengths, standard and extra height. Fixing is as per the standard 6" type.

Swingaway 8" Jockey Wheel. Fixing and operation is as per the 6" swingaway. Also available with a loose swingaway bracket that you can weld in the position that best suits the trailer drawbar height.

10" LIGHT TO VERY HEAVY DUTY: 160kg to 1250kg Static Load.

Standard 10" Pneumatic Jockey Wheel. 160kg Capacity.

A removable jockey wheel with a capacity limited by its inflatable tyre. Popular on small boat trailers where a larger 'footprint' is an advantage in soft sand. Seen on many small camper trailers too.

Swingaway 10" Pneumatic Jockey Wheel. 160kg capacity.

As above but with a swingaway type mounting bracket welded in place. The swingaway bracket may be attached as per the 6" swingaway type (See above)

Easymover 10 Solid Cushion Jockey Wheel. 750kg capacity.

Use this jockey wheel to crank and steer your camper or caravan into tight spots. No swingaway type is available. **DO NOT USE THIS UNIT TO MANOUEVER YOUR TRAILER/CARAVAN ON SLOPING GROUND. THE WEIGHT OF THE LOAD MAY OVERPOWER YOU, WITH FATAL RESULTS.**

10" Heavy Duty Jockey Wheel. 1250kg capacity

Suitable for large plant trailers. The highest capacity jockey wheel we sell and for good reason. It would be unsafe to try and handle anything with a drawbar weight exceeding 1250kg. Available with standard and loose swingaway brackets for fixing at the desired height.

Jack Stands

We recommend fitting a **Jack Stand** in place of a Jockey wheel on trailers with a high drawbar weight, as attempting to maneuver a trailer weighing several tonnes on a jockey wheel could be very dangerous. We have a wide range of Jack Stands in capacities from 650kg to 5 tonnes. Most of these stands can be fitted with a swingaway mounting bracket, and the majority are raised and lowered by way of a side mounted handle. A few models feature an additional 'drop down leg' that is released by simply removing a pin in order to gain extra lift. One model is made especially tall and is suitable for removing slide on campers etc. from utes.

Stabiliser Legs

We have a full range suitable for keeping your caravan or camper 'on the level'. All require welding to the frame of the caravan or camper. The traditional stabilizer legs come in two lengths, 500mm for most caravans and 600mm long for the higher off road campers and caravans. Both lengths are in turn available with an additional small wheel fitted in the rear of them and this prevents the rear of the caravan/camper bottoming out on kerbs etc.

We also sell the newly available swingdown legs in closed lengths ranging from 410mm up to 600mm and offering an additional 240mm extension in addition to the closed length. Be sure to measure the distance available from your frame to the ground with the caravan/camper on level ground in order to make the correct selection. These legs all have a capacity of 350kg each.

All Trailer Spares are major Manutec jockey wheel stockists and Manutec is a name that you can always trust to support you and your trailer.

All Trailer Spares and The Trailer Place stock a full range of Manutec products and spare parts.

© Copyright – All Trailer Spares (Australia) Pty Ltd